

Attorney Docket No. 74953/11664

Entitled:

REMOTE ACCESS OF AN AIRPORT AIRFIELD LIGHTING SYSTEM

Joint Inventors:

Edwin K. RUNYON
270 Halligan Avenue
Worthington, OH 43085

Jess MURPHY
845 Buehler Drive
Delaware, OH 43015

Stephen RAUCH
10603 Allen Road
Pickerington, OH 43147

Joe POKOJ
6693 Pine Hollow Drive
Westerville, OH 43082

John C. STUTZ
8116 Chutney Road
Blacklick, OH 43004

Assignee:

Siemens Airfield Solutions
977 Gahanna Parkway
Columbus, OH 43085

Submitted by:

Eric D. Jorgenson
Reg. No. 46,002
Arter & Hadden, L.L.P.
1100 Huntington Building
925 Euclid Avenue
Cleveland, OH 44115-1475
(216) 696-1100

FILE NO. 74953/11664

PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

REMOTE ACCESS OF AN AIRPORT AIRFIELD LIGHTING SYSTEM

REMOTE ACCESS OF AN AIRPORT AIRFIELD LIGHTING SYSTEM

BACKGROUND OF THE INVENTION

5 TECHNICAL FIELD OF THE INVENTION

This invention is related to airport airfield lighting systems, and more specifically, to systems which monitor such airfield lighting systems and remote access provided thereto via the Internet.

10 BACKGROUND OF THE ART

The future of aviation is undergoing a massive technological change with the use of Global Positioning System (GPS) technology. This change not only affects large air carrier airports, but also the smaller general aviation airports located in remote areas or small towns. Higher levels of funding are also becoming more available for general aviation airports.

It is anticipated that changes in federal regulations under the FAA (Federal Aviation Administration) will stipulate that the FAA no longer buy and maintain the approach equipment. Equipment will be funded by the FAA, however, the equipment will need to be installed and maintained by local airport maintenance staff and/or out-sourced to a maintenance contractor for support. This change from a centralized federal program to a localized standalone operation presents a new problem for approach lighting systems for general aviation airports. Not only will the local airports be held responsible for the maintenance of the airfield lighting and related systems, but they will need to provide the support contracts. Furthermore, in those remote areas where technically-capable maintenance personnel may not be readily available, other means are needed to ensure that the airport has a safe and operational airfield lighting system.

What is needed is a system which provides local monitor and control of the general aviation airport airfield lighting system while also offering remote portal access to the local system by authorized users for periodic review of the system data which indicates the viability of the airport system. Furthermore, the local system needs an

automatic notification feature for automatically notifying selected users when system faults occur. Still further, what is needed is a centralized general aviation monitoring system which connects to monitor a number of remote general aviation airport airfield systems, including runway and approach lighting systems, etc., such that authorized individuals can access the remote systems from anywhere, and at any time.

SUMMARY OF THE INVENTION

The present invention disclosed and claimed herein, in one aspect thereof, comprises remote monitor and control of an airfield lighting system. A processing system
5 local to the airport is provided in communication with the airfield lighting system for monitor and control thereof, the airfield lighting system producing airfield information for processing by the local processing system. The local processing system connects to a global communication network such that the airfield lighting system information is accessed from a remote location disposed on the global communication network.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
22

BRIEF DESCRIPTION OF THE DRAWINGS

For a more complete understanding of the present invention and the advantages thereof, reference is now made to the following description taken in conjunction with the accompanying drawings in which:

5 FIG. 1 illustrates a block diagram of a remotely accessible general aviation monitor and control system;

 FIG. 2 illustrates a flow chart from the perspective of a customer/client when accessing the disclosed system;

 FIG. 3 illustrates a flow chart from the perspective of maintenance support
10 personnel when accessing the disclosed system;

 FIG. 4 illustrates a flow chart of the operation of the airport notification system, according to a disclosed embodiment;

 FIG. 5 illustrates a flow chart of the operation of the remote airport monitor and control system;

15 FIG. 6 illustrates a flow chart of operation from the perspective of the control center a user accesses the disclosed system;

 FIG. 7 illustrates a user interface of an authorization web page to the control center website;

 FIG. 8 illustrates a follow-up web page to the authorization web page showing
20 various data parameters which can be accessed by a user; and

 FIG. 9 illustrates a database structure, in accordance with a disclosed embodiment.

DETAILED DESCRIPTION OF THE INVENTION

The disclosed system architecture consists of several components combined to effect a system that monitors the status of airfield lighting equipment, and reports status and failure condition information to a central control center. The control center then utilizes this information to dispatch service personnel to the airfield for corrective action. The control center also provides historical and trending analysis for the airfield equipment being monitored for the client.

The disclosed system is not limited to airfield lighting systems, but can accommodate any airport systems, including fire alarm systems, security systems, etc. In those situations where general aviation airports have conventional remote monitoring systems already in place, the disclosed system is operable to provide redundant control and measurement capability of the existing data points, or even displacing the conventional system in its entirety. For example, the FAA (Federal Aviation Administration) purchases and provides airfield equipment, e.g., approach lighting systems (ALS) and precision approach path indicators (PAPIs) for some, but not all, aviation airports, and the FAA currently elects to support (i.e., maintain and monitor) such approach systems for those selected airports. Regional FAA offices throughout the U.S. provide oversight of the respective ALS and PAPI systems utilizing a remote maintenance monitor (RMM) system for monitoring selected parameters of the regional airports. The associated RMM hardware and software of the FAA system is expensive. Where such an FAA implementation exists, the disclosed system can provide either redundant monitor and control capability of the various data points with access from the various networked entities, as will be described in greater detail hereinbelow, or preferably displace the FAA system entirely with a more robust and cost effective solution. In the least, substantial improvements in remote accessibility can be provided for the RMM data points via a redundant implementation of the disclosed system.

Referring now to FIG. 1, there is illustrated a block diagram of a remotely accessible general aviation monitor and control system, according to a disclosed embodiment. An airport 100 comprises a runway 102 which has associated therewith a number of airfield lighting system lights 104 whose electrical parameters are under control of a respective control and monitor unit 106. For example, the light interface control and monitor unit 106 may provide constant current control by way of a constant

current regulator (CCR). Other means may be used to control each of the lights 104 of the runway such as voltage control devices. Note that the disclosed architecture is not restricted to runway lighting systems, but can be implemented to monitor and control any airport systems connect thereto. Examples include, as indicated hereinabove, ALS and PAPI systems, RMM systems, runway edge identifier lights, rotating beacons, etc.

The light interface units 106 each connect to a server 108 via a communication path 107 to facilitate the communication of monitor and control information to and from the light interface units 106, and to store data parameters related to the airfield lighting system of that particular airport 100. The communication network 107 between the control units 106 and the server 108 can be any conventional architecture which provides such connectivity. The medium can be optical fiber, metal wire, and even communication signals which are modulated onto power signals for transmission over power cables (e.g., X10 technology). The server 108 connects to an airport network interface device 110 for communication via an external global communication network (GCN) 112, e.g., the Internet, and offers access to the remote airport 100 from any node connected thereto. The airport network interface device 110 can be that which accommodates any technology for providing such communication capabilities, for example, DSL, cable modem access, ISDN, analog modem, T1, etc.

It can be appreciated that where global access is provided via the GCN 112, more secure measures may be needed to prevent unauthorized access to the server 108 and connected systems of the remote airport 100. For example, a firewall system 114 may be implemented to prevent such unauthorized access. The firewall system 114 connects to the airport network interface device 110 such that all incoming communication traffic is routed therethrough, and then to the server 108 along a path 116. Although the firewall system 114 is illustrated as a separate block, it can be consolidated into the server 108 such that all incoming traffic is routed directly from the airport network interface device 110 along a path 118 to the server 108. The firewall system 114 can also be a part of the airport network interface device 110, as can be obtained conventionally in conjunction with, for example, DSL modems, cable modems, ISDN modems/routers, etc.

For airport equipment which may be sited at locations too distant from the airport server 108 such that hard wire communication is impractical, a wireless communication technology may be implemented. For example, a piece of airfield lighting equipment 101 located at a remote airport location can be configured to accommodate a wireless

transmitting device (not shown) which utilizes an antenna 103 for wirelessly uploading data to the airport server 108, and downloading information from the server, where desired. In this embodiment, radio frequency communication may be utilized.

5 A control center 120 disposed on the GCN 112 provides centralized control and monitor functions for the remote airport 100, and a plurality (2,...,N) of remote airports 122. The control center 120 comprises a central data server 124 which stores all control and monitor data from the remote airports 100 and 122. The data server 124 interfaces to the GCN 112 via a network interface device 125, which network interface device 125 has capabilities similar to that disclosed in reference to network interface device 110 of the
10 remote airport 100. The central data server 124 also connects to a server control block 126 which provides the control center user interface for the disclosed airport system, including database access of the central data server 124, application and data control for the remote server 108 of the airport 100 through the GCN 112 (and other alternative communication methods disclosed hereinbelow), and remote servers (not shown) of the
15 remote airports 122.

Communication with the remote airports 100 and 122 is accomplished utilizing a number of methods. As indicated hereinabove, the control center 120 communicates with the remote airports 100 and 122 via the packet-switched GCN 112, or in instances where the GCN 112 may be inoperative, through a circuit-switched Public Switched Telephone
20 Network (PSTN) 128. A modem 130 provides the interface for communicating over the PSTN 128, and using a switching device 132, alternatively facilitates communication over a wireless path 133, e.g., a cell phone, should the PSTN 128 become inaccessible.

The remote airport 100 has a compatible modem 134 and switching device 136 for utilizing either the PSTN 128 or the wireless path 133, if the GCN 112 becomes
25 inaccessible. These various methods of maintaining communication with the airports 100 and 122 offer a variety of ways in which to maintain communication between the control central 120 in order to provide control parameters to airport server 108 and data parameters to the subscriber and maintenance contractor under many communication failure conditions. It can be appreciated that communication with the local maintenance
30 contractor may also be accomplished directly from the airport server system 108 through the PSTN 128, or the GCN 112, or wireless path 133, in contrast to the notification coming indirectly from the remote airport through the control center 120. In this scenario, the fault notifications are stored in the remote server 108 and eventually

transmitted to the data server 124 of the control center 120 for archiving and processing, and provided to the subscriber in accordance with the subscribed level of service.

Other nodes can access the remote airport 100 in accordance with various functions. For example, a sales/marketing node 138 has one or more computers 140
5 operatively connected to the GCN 112 through a sales network interface 142. The control center 120 hosts a website which is accessible by any node on the GCN 112. However, access to contents of the website is restricted to authorized users by use of a unique password or access code issued to each user. The sales/marketing node 138 is provided access to the website to facilitate illustration of the novel system to potential customers.
10 Note that there may also be a plurality of such sales/marketing nodes 138 disposed on the GCN 112 which are provided access to the airfield lighting systems of the one or more remote airports (100 and 122).

A contractor node 144 for maintenance personnel who contract to provide support to the remote airport 120 may also be disposed on the GCN 112 to access the website
15 provided by the control center 120. The contractor node 144 comprises a computer 146 (or other conventional network user interface device) which can access data associated with the remote airport airfield system to determine the status of the airfield lighting system, a contractor network interface device 148 for interfacing to the GCN 112 to facilitate accessing the website provided by the control center 120, and optionally a
20 modem 150 can be provided as a backup means to the GCN 112 communication path for accessing the airport 100 via the PSTN 128. It can be appreciated that the contractor node 144 may also comprise a wireless solution 152 (e.g., cellular telephone) to facilitate wireless communication directly with the airport system 108 via the wireless path 133 if communication to the website is inaccessible via the GCN 112. However, the primary
25 communication path is via the GCN 112 to the central control center 120.

A customer node 154 also disposed on the GCN 112 is provided access to the data via the website hosted by the control center 120. The customer node 154 utilizes a customer computer 156 (or other network user interface device) which communicates to the control center website through a conventional customer network interface device 156
30 across the GCN 112.

The central control center 120 also includes a network access security system to preclude unauthorized access thereto from the various communication paths which provide access thereto. For example, a firewall system is implemented where access via

the GCN 112 is provided. Where dial-up access is provided, various security measures can be utilized, e.g., automatic call-back, user ID/password, etc. Where packet-switched networks are provided (e.g., intranets and extranets), access can be restricted to the unique network interface card ID of the authorized user.

5 Referring now to FIG. 2, there is illustrated a flow chart from the perspective of a customer/client when accessing the disclosed system. When the client subscribes to the disclosed airport system, they are issued at the time of subscription (or prompted to generate at a later time when first accessing the website) an authorization code for future use in logging in to the website in order to access the airport data points. Flow begins at a
10 function block 200 where the client logs in to, e.g., a mail server (either local or remote mail server) which provides e-mail access to any node on the GCN 112. Flow is then to a decision block 202 to determine if any faults detected at the remote airport have caused e-mail messages to be generated. (Note that notification is not restricted to e-mail messaging, but can be by any number of communication mechanisms, as indicated
15 hereinbelow.) These e-mail messages can be transmitted to both the client and the maintenance support personnel in order to keep the client informed of any faults detected by the remote airport system. The message, in whatever format, can also be generated for delivery at a time when transmission costs are more favorable. For example, where telephone switched-circuit technology is used, there exist times when the cost of making
20 such a transmission are less. Of course, the decision to delay such a notification is based upon several factors, for example, the type of failure, such that a nominal failure of a single light may result in the notification being delayed, while a total failure of the all systems causes immediate notification to occur. If an alert was transmitted to the client e-mail address, flow is out the "Y" path to a function block 204 to take action based upon
25 the alert. The action could include automatically connecting the client node to the website provided by the control center 120 such the client can quickly log in and view the alert and its associated fault, as indicated by the output of function block 204 flowing to a function block 206. If no e-mail message was received, flow is out the "N" path to a function block 206 where the client accesses the website web page. Flow is then to a
30 function block 208 where the client must enter authorization information in order to gain access to further data related to the remote airport 100. The client can then view the airport data in accordance with the level of service subscribed during the subscription period, as indicated in a function block 210. Note that the disclosed system need not have

a level-of-service program such that the client is provided with total access to all information related to the remote airport 100. Flow is to a function block 212 where the client then logs out of the website, and the process reaches a Stop point.

Referring now to FIG. 3, there is illustrated a flow chart from the perspective of maintenance support personnel when accessing the disclosed system. Flow begins at a decision block 300 where the alert notification monitor system at the maintenance support node 144 continually operates to check for a received alert. The alert notification system includes e-mail, facsimile, a pager, notification via a cellular telephone, etc. If an alert has not been detected, flow is out the "N" path and loops back to the input to continue monitoring for a received alert. If an alert has been received, flow is out the "Y" path to another decision block 302 to determine if the GCN 112 is accessible such that the maintenance personnel can access the remote airport 100 via the website provided by the control center 120 in order to obtain further information of the fault condition. It can be appreciated that this accessing step need not be performed prior to the maintenance personnel being dispatched to the remote airport 100 to correct the fault. However, this feature allows the maintenance staff to better prepare for correcting the fault condition, if it is of a kind which requires expensive replacement parts which may not be stored at the remote airport, or perhaps requires special test equipment in order to troubleshoot and resolve such a fault condition. If the GCN 112 is not accessible, flow is out the "N" path to a function block 304 where the support personnel at the contractor node 144 can use an alternative communication system to obtain more detailed information related to the type of fault condition. For example, a circuit-switched direct-dial connection may be implemented such that the contractor node 144 can communicate directly with the control center data server 124 through the contractor modem 150 via the PSTN 128. If a cell phone is used to contact the control center 120, communication can be through the wireless path 133 using air protocols (WAP - Wireless Application Protocol, and Wireless Java) to the control center modem 130. For example, where the cell phone has a display capability, the contractor can access the control center website using the cell phone such that web clipping can provide a reduced HTML (or other web page development language) visual or text presentation to the contractor regarding the particular fault condition, as indicated in a function block 314. Alternatively, support personnel at the contractor node 144 can communicate directly with remote airport server 108 via the wireless path 133 established between the contractor node antenna 152 and

the remote airport antenna 135. These and other wireless Internet technologies accommodate the wireless transmission of Internet information according to handset geolocation information. (Note that alternative wireless mobile technologies include fixed wireless, broadband wireless (e.g., LMDS - Local Multipoint Distribution System, and MMDS - Multipoint Multichannel Distribution System) and satellite.) Other methods of communication connectivity can be implemented, for example, an intranet or extranet implementation.

Flow continues to a function block 316 where the maintenance personnel are dispatched to the remote airport 100 to correct the fault condition and clear the alert signal. Flow continues to a function block 318 where the support personnel then log the fault information and the repairs performed by entering this information into the airport server 108. The airport server 108 will then upload this information during the next programmed upload cycle. Notably, this repair information may also be entered directly to the control center server 124 via the control center website, where the repair technician logs in to the control center website using any available node in communication therewith, and enters the repair information into a predetermined repair form for archiving. What is important is that this repair information is ultimately archived in the control center server 124 for historical trending related to airfield parts and equipment which have failed. Note that the database of repair information can also be used for inventory control purposes, as discussed in greater detail with respect to FIG. 9. In accordance with the level of service provided to a subscribing customer, this trending information may also be made available to the customer who logs in via the control center website.

Referring again to decision block 302, if the GCN 112 is accessible, flow is out the "Y" path to a function block 306 where the repair technician logs in to the local system at the contractor node 144. Flow continues to a function block 308 where the technician accesses the control center website in order to obtain further information about the fault condition. The technician is then prompted for the authorization information, as indicated in a function block 310, in order to gain access to data related to the fault at the remote airport 100. The technician is then provided the fault information in accordance with the subscribed level of service, as indicated in a function block 312. In an alternative implementation, the e-mail message provides a hyperlink directly to the control center website, or in lieu thereof, provides a detailed description of the fault

condition such that the technician is not further required to log in to the control center website to obtain more detailed fault information. In such an implementation, the e-mail message can be generated to automatically provide all of the fault information needed to properly address the fault condition. As part of generating the e-mail message, the
5 control center data server 124 is automatically accessed to retrieve fault data sufficient to provide the technician the information necessary in correcting the fault condition. This e-mail function can operate in lieu of, or in conjunction with the notification mechanism discussed hereinabove with respect to function block 314. Flow is then to the function block 316 where the technician reports to the remote airport 100 to make repairs and clear
10 the alert. After making repairs, and in order to track failure history, the technician logs the repair information, as indicated in the function block 318. The maintenance process flow then reaches a Stop block.

Referring now to FIG. 4, there is illustrated a flow chart of the operation of the airport notification system, according to a disclosed embodiment. Flow begins at a
15 decision block 400 where the fault notification system of the control center 120 processes recently-uploaded data from the remote airport server 108. If the data indicates that all parameters are within predefined limits, flow is out the "N" path, and loops back to the input to continue monitoring the data. If the data indicates that one or more monitored parameters are out of limits, the corresponding faults are noted. When a fault is detected,
20 the control center system then accesses a database of the data server 124, which database may be the same database which includes the measured parameters of the remote airport 100, and retrieves maintenance personnel information associated with the particular remote airport 122 reporting the fault, as indicated in a function block 402. Additional airport system information may be retrieved at this time in anticipation that some or all of
25 this information will eventually be forwarded to the repair technician as part of the notification alert, or perhaps in response to a later query by the technician for more detailed fault information. Flow is then to a function block 404 where the alert message is generated and transmitted to the repair technician. As mentioned hereinabove, any number of communication methods can be utilized to signal the repair technician at the contractor node 144, including but not limited to, transmission by e-mail via the GCN
30 112, a pager, cellular phone, personal data assistant, conventional telephone messaging, voice over IP (VoIP), etc. Flow is to a decision block 406 to determine if the GCN 112 is accessible. If not, flow is out the "N" path to utilize any one or more of the

abovementioned communication methods to alert the technician to the fault condition at the corresponding airport, as indicated in a function block 414. Flow then continues to decision block 416 to determine if the repair technician has corrected the fault condition and cleared the alert. If not, flow is out the "N" path to the input of decision block 416 to
5 continue monitoring the condition until the alert is cleared. If the repair technician has repaired the fault and cleared the alert, flow is out the "Y" path of decision block 416 to a function block 418 where, after the technician has logged all information related to the fault and correction thereof, the control center 120 uploads data from the remote airport server 108 at a predetermined time. This data is then accessible to any authorized user
10 via the control center website. Flow then loops back to the input of decision block 400 to continue monitoring all remote airport servers 108 (and servers of the corresponding plurality of airports 122) for transmitted fault information.

Referring again to decision block 406, if the GCN 112 is accessible, flow is out the "Y" path to a function block 408 where a message is generated and transmitted (e.g.,
15 an e-mail message) to the repair technician at the contractor node 144. Note that alert notification by e-mail messaging may provide a sufficient response time for many fault conditions. However, in those instances where more catastrophic failures occur, for example, all airfield lights fail, the fault condition may need to be tagged in accordance with a priority hierarchy. Such a catastrophic failure will then be tagged a high priority
20 failure, in which case e-mail messaging could be utilized in conjunction with one or more other alert notification methods disclosed hereinabove, or a more immediate notification method, such as paging the repair technician, could be used in lieu thereof. Therefore, if the fault condition is considered a higher priority fault condition, flow is out the "Y" path of decision block 410 to function block 414 to use an alternate communication method in
25 order to facilitate faster response by the repair technician. Flow from this point follows the discussion detailed hereinabove. If the fault condition is deemed to not be of a high priority, flow is out the "N" path of decision block 410 to a decision block 412 to determine if a confirmation has been received. This can be an optional step to ensure that the repair technician has acknowledged receipt of the alert e-mail message. If not, flow is
30 out the "N" path to function block 414 to use an alternative communication method of notifying the repair technician, and flow therefrom follows the discussion detailed hereinabove. If an e-mail confirmation was received, indicating that the repair technician acknowledged receipt of the e-mail alert, flow is out the "Y" path of decision block 412

to decision block 416 to determine if the repair technician has cleared the fault condition (i.e., reset the alert flag by repairing the fault condition). Discussion of subsequent branch conditions and steps follows that which was disclosed hereinabove with respect to decision block 416.

5 Referring now to FIG. 5, there is illustrated a flow chart of the operation of the remote airport monitor and control system. Flow begins at a decision block 500 to determine if a fault condition at the remote airport has occurred, and been detected. If so, flow is out the "Y" path to a function block 502 to generate an alert message in accordance with programmed notification parameters, which includes extracting data
10 from the airport database server 108 in order to identify and notify the corresponding repair technician of the particular fault condition. Note that there can be more than one contractor supporting the various aspects of the remote airport airfield system. For example, there can be a mechanical contractor notified to correct mechanical failures, an electrical contractor which is notified to correct power failures, electronics contractors to notified to correct computer and control system failures, HVAC contractors to correct
15 heating and cooling failures which may be associated with sustaining larger remote airport systems, etc. If no fault is detected, flow is out the "N" path of decision block 500 to a function block 504 to periodically monitor selected data points of the airport airfield system. The rate at which the data points are acquired is performed in accordance with predetermined programmed criteria. Once the data is acquired from the various
20 measurement points, the data is stored on the airport server 108, as indicated in a function block 506. Flow is then to a decision block 508 to determined if it is time to establish communication with the control center 120 in order to upload the latest airport airfield data to the control center server 124. If not, flow is out the "N" path, and loops back to the input of decision block 500 to continue monitoring for a fault condition. Note that the
25 fault condition may be determined in accordance with the latest set of data acquired by the airport server 108 from the data points, or the fault condition may be directly transmitted to the airport server 108 from the faulty device when the fault occurs, bypassing the periodic data acquisition step routinely executed by the server 108. Such
30 an immediate notification system could use discrete devices distributed proximate to the data points to be measured such that a processor associated therewith continuously monitors the data wherein an alert can be transmitted as soon as any measured data point falls outside predetermined limits.

Note that it can be appreciated in cases where the data point is remotely located from the airport server 108, a standalone smart device can be utilized having a processor which is programmed to monitor the data points, and to communicate data and alerts to the airport server 108 according to prescribed time intervals, or on a realtime basis.

5 Referring again to decision block 508, if it is time to upload data from the airport server 108 to the control center server 124, flow is out the "Y" path to a function block 510 to establish a communication connection to the control center 120. As mentioned hereinabove, the connection can be by any number of methods, however, in this embodiment, communication is via the GCN 112. Flow is then to a decision block 512 to
10 determine if the GCN 112 is accessible. If not, flow is out the "N" path to a function block 514 to utilize an alternative communication system as disclosed hereinabove, or in accordance with many conventional communication architectures. Flow is from function block 514 to the input of a function block 516 to upload the data to the control center server 124 by the established communication method. If the GCN 112 is accessible, flow
15 is out the "Y" path of decision block 512 to the function block 516 to upload the data across the GCN 112 to the control center server 124.

It can be appreciated that the disclosed system also provides the capability of downloading updated programming to the remote airport server 108. For example, if an improved control and data acquisition program update had become available, the update
20 could be downloaded from the control center server 124 to the remote airport server 108 at the time of uploading the data from the airport server 108. Alternatively, the updated program could be downloaded at times when airport traffic is determined to be the least likely to occur such that any possible programming problems would not interfere with operation of the remote airport system. Continuing with the flow chart, flow is then to a
25 decision block 518 to determine if updated programming is available for download. If not, flow is out the "N" path, and loops back to the input of decision block 500 to continue monitoring of fault conditions. If updated programming is available for download, flow is out the "Y" path of decision block 518 to a function block 520 to commence the program transfer. Flow is to a function block 522 to then restart the
30 program code, where necessary, and where airport airfield operation is least likely to be interrupted should a program problem occur. Flow then loops back from function block 522 to the input of decision block 500 to continue monitoring for fault conditions.

Referring now to FIG. 6, there is illustrated a flow chart of control center system

operation from the perspective of the control center when a user accesses the disclosed system. Flow begins at a function block 600 where a user establishes communication across the GCN 112 to the control center website. Note the user can be a user from the customer node 154, the maintenance contractor node 144, the sales/marketing node 138, a user from the remote airport 100, etc. Connectivity can be established from virtually any user disposed on the GCN 112 who has a network user interface device which executes a communication application (e.g., a browser) compatible for interfacing to the control center website. It is also conceivable that the data stored on the control center data server 124 is accessible using a file transfer protocol which retrieves information in a non-HTML (or browser) format. The user is then prompted for authorization information, as indicated in a function block 602. Flow is to a decision block 604 to determine if the entered authorization information is valid. If not, flow is out the "N" path to a function block 606 to notify the user that an error has occurred, and to, for example, re-enter the authorization information. Flow then loops back to the input of decision block 604 to check the entered authorization again. If multiple entry failures have occurred, the user can be locked out from further access and instructed to contact the system provider.

If the entered authorization information is valid, flow is out the "Y" path of decision block 604 to a function block 608 to perform a database query in accordance with the valid authorization information. The query establishes the association with the data which is to be presented to the authorized user, and where levels of service are provided, presents only that information to which the user is subscribed. For example, if the authorization information indicated a user at the sales node 138, the data presented to prospective customers could be that associated with a demonstration application operating on the accessed control center server 124. Alternatively, or in conjunction therewith, the sales staff can be provided access to actual data from the remote airport 100. In any case, the level of access provided to the extensive features of the disclosed airport system is provided in accordance with the authorization (or login) information. Flow then reaches a Stop block.

Referring now to FIG. 7, there is illustrated a user interface of an authorization web page to the control center website. The user interface is via a conventional network communication program (e.g., a web browser). The authorization web page 700 contains standard features for providing authorized access to further information. For example, the web page contains a site path information field 702 which indicates the current

Uniform Resource Locator network address of the web page 700. A menu field 704 provides various application functions which can be used by the user. A navigation bar 706 allows the user to move both forward and back through web pages which have already been downloaded from the control center data server 124 to the user computer (e.g., computer 140, 156, etc.). The web page 700 also includes an address field 708 which allows the user to enter a network address of a node on the GCN 112 to which the user may want to connect. An active link field 710 presents the network address of one or more active links embedded into the web page.

A main body area 712 of the web page 700 comprises text 714 which may, for example, provide a greeting to the user, and instruct the user to perform certain steps in order to obtain further information. In this scenario, the text 714 instruct the user to enter an authorization code in a code field 716 before further access is provided. As indicated hereinabove, the authorization code is provided to the user (e.g., the customer, contractor, sales person, etc.) when an account is opened for the customer. The authorization code is unique to each entity, but may provide access to the same information stored in a server database (e.g., the database of the control center data server 124). The authorization code may be a single alphanumeric character string, or could be a combination of a user ID and password, or any other type of conventional access authorization methods provided by network web sites.

The authorization web page 700 may also include an ad space 718 which provides fixed or rotating advertisements to the user. The ads 718 comprise information which informs the user of new updates to system, or other informational functions such as products associated with the system provider, etc. It can be appreciated that where cookies are allowed on the user computer system, whether it be the customer, contractor, sales personal, etc., the ads 718 can be customized to provide information of interest to the particular user. For example, if the user is a customer at the customer node 154 connected from California, and the remote airport is located in Minnesota, the ads 718 presented could be triggered to such geographic information to provide weather reports based upon seasonal changes, which are not a concern in California, but which may significantly impact operation of the airport airfield system in Minnesota. Similarly, where the user is a maintenance contractor, the ads 718 could be trigger in response to the contractor cookie information to present recent updates in system hardware or software which are of interest only to the contractor, or advertise recent developments in

troubleshooting hardware, or airfield lighting improvements which could be purchased by the system provider.

Note that this customized advertising can also be triggered based upon the unique user authorization code, such that the information is provided on a subsequent web page, and in greater detail according to specific user interests and the remote airport(s) being monitored. The extent of the messaging via the advertisement area 718 can accommodate a wide variety of information including paid advertising for related products.

Referring now to FIG. 8, there is illustrated a follow-up data web page 800 to the authorization web page 700 showing various data parameters which can be accessed by a user. The primary difference between the information of this web page and the previous authorization web page 700 is contained within the body area 712. After the user authorization code has been validated, the data web page 800 is presented to the user with various data parameter information about the status of the remote airport airfield system selected. If the remote airport airfield system had ten CCR front-end systems for monitor and control of airfield lighting, data regarding each CCR could be listed on the data web page 800 along with an associated status field. For example, a first CCR 802 is listed, and has associated therewith a data field 804 in which a corresponding data parameter can be placed in a numerical format to indicate the state of that light system. Alternatively, the data can be automatically interpreted by software such that a general status text (e.g., "ok" or "failed") is provided, when the particular CCR 106 is operating properly. Other data can also be provided, for example, measured parameters related to dielectric integrity 806 of the series system are retrieved from the control center data server 124 and inserted into a corresponding dielectric field 808 for presentation to the user. Additionally, an information area 810 can be provided for presenting detailed information to the user. Since the user has already passed the authorization stage, information provided in the information area 810 can be sufficiently detailed, e.g., to inform the user regarding account information, hardware/software historical data, etc. It can be appreciated that the information provided herein is solely at the discretion of the system provided and the user.

In an alternative embodiment, the type of information provided can be based upon the authorized user. For example, if the user is a sales person, the level of detail provided in the data fields 804 may be in a go/no-go format, e.g., "ok" or "failed, whereas if the user was a repair technician, the data would be actual numerical values which are more

useful in determining the true state of the remote airport system. It can be appreciated that numerous options can be provided to the specific users of the web portal based upon a number of factors, and the availability of the options can be based upon a subscribed level of service, or each user can have full access, etc.

5 Where the customer has several remote airports 122 under monitor and control utilizing the disclosed system, the web page 800 can include data for both airports on the same web page 800 if sufficient web page real estate exists, or an active link 812 can be provided, which when selected by the user, presents another web page (not shown) of data and information associated with that remote airport 122.

10 Referring now to FIG. 9, there is illustrated a database structure 900 of account information and data parameters which may be archived, in accordance with a disclosed embodiment. As indicated hereinabove, numerous pieces of information may be stored in association with a user in the database of the control center data server 124 for later retrieval and presentation. For example, in this particular database example, an
15 authorization code field 902 provides a primary association with the remote airport 100 by linking the authorization code with data of the particular remote airport 100. When the user enters an authorization code, a variety of associated information is made available for presentation to the user. This associated information is also accessed when a fault condition is detected, such that when an airport code 903 is known, the
20 corresponding contact information for the repair technician (and/or other designated persons) can be retrieved for establishing communication thereto. As illustrated, the contact information comprises an e-mail field 904, a pager field 906, and telephone number field 908. Other contact information can also be provided, as mentioned hereinabove, for example, a facsimile number, a cellular telephone number, a network
25 address to a PDA device, etc.

 The database 900 also includes a service level field 910 which defines the level of subscribed service, where such an option is provided. For example, a first customer 912 (Cust1) may have subscribed to a level of service (e.g., level 1) which includes presenting status data parameters 911 of a general nature (e.g., "ok") with respect to a corresponding
30 remote airport airfield system, and does not present, for example, trending information which is provided at a different level (albeit more costly) of service (e.g., level 4), specific parameter values, etc. Many different options for data manipulation can be provided limited only by the robustness of the underlying applications which process the

data and support the control center web site. It can be appreciated that the information presented to the a repair technician (Repair1) associated with a repair field 914 can be more specific to facilitate problem resolution. Note that a single customer (Cust1) may have the same authorization code for accessing multiple remote airports (e.g., aaaa and
5 xxxx) for which service is subscribed.

The database associated with the data server 124 can also store maintenance and parts information such that as the maintenance technician orders and uses parts or components from inventory, the part can be tracked as to the location at which it is used. The maintenance database can also operable to track the inventory to automatically
10 trigger replenishment by notifying an individual to order sufficient parts to bring inventory of those parts or components back to a minimum level. The data server is also operable to automatically notify, for example, a central inventory warehouse to ship a replacement part when the cause of a fault is detected by the disclosed system. The data server 124 can also cross-check the availability of the failed component against an
15 inventory database of parts or components stored locally to the airport to first determine if the part can be obtained from a local inventory or needs to be ordered-in from a remote location.

Although the preferred embodiment has been described in detail, it should be understood that various changes, substitutions and alterations can be made therein
20 without departing from the spirit and scope of the invention as defined by the appended claims.